



A POLI-TAPE GROUP Company

# DIGIT 60 P White Gloss Cast Killer

## Product Information

Polymeric soft PVC Film (white gloss, 60  $\mu$ ) with grey-coloured solvent based acrylic adhesive (permanent), laminated on a two-sided PE-coated silicone paper (145 g/m<sup>2</sup>).

The PVC offers an excellent dimensional stability.

The grey-coloured solvent based acrylic adhesive ensures a very good opacity.

Designed to be highly resistant to solvent ink aggression during printing process and to guarantee very good printing performance on any solvent and eco-solvent based ink-jet printer.

Particularly suitable for application on flat, curved and corrugated surfaces. No adhesive residue after removal, if correctly applied.

## Shelf Life

2 years when stored in the original packaging between 20°C and 25°C at 50% relative humidity.

## Recommendations for laminating

Please ensure the print is perfectly dry before laminating. We suggest to let the material dry for at least 48 hours after printing.

## Technical Data

<b>Carrier:</b>	Polymeric soft PVC, highly stabilized, calendered
<b>Thickness:</b>	60 $\mu$ +/- 5 %
<b>Adhesive:</b>	grey-coloured solvent acrylic, permanent
<b>Adhesion:</b>	7,5 N/cm
<b>Liner:</b>	two-sided PE-coated silicone paper (144 g/m <sup>2</sup> )
<b>Application temperature:</b>	+10 - +40 °C
<b>Temperature durability :</b>	- 40 - +80 °C
<b>Outdoor durability:</b>	5-7 years (unprinted film)

## Standard Dimensions

1370 mm x 50 m

1520 mm x 50 m

## Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.

### KEMICA S.r.l.

Via F.lli Rusjan, 76 - Frazione Rupa  
34070 Savogna d'Isonzo (GO) - ITALIA

Phone: +39 0481 882 501

Fax: +39 0481 882 440

E-Mail: [info@kemicasrl.it](mailto:info@kemicasrl.it)

Internet: [www.kemica.it](http://www.kemica.it)

12/09/2016

The following technical details are issued to the best of our knowledge, however, without any responsibility. Due to the varied and application-related influences the product liability can only be applied to unprocessed material. Therefore, we highly recommend that before every usage a test should be conducted on the original material.