



A POLI-TAPE GROUP Company

# TEC FLOOR 800

## Product Information

Embossed polycarbonate (transparent matt, 125  $\mu$ ) with a clear solvent based acrylic adhesive (permanent), laminated on a siliconized polyester liner (50  $\mu$ ).

Especially designed for floorgraphic applications with anti-slippery character and scratch resistant surface for mid-to long-term floor decoration and advertising (airports, railway stations, shopping centers).

Anti-Slip Certificate available.

## Shelf Life

2 years when stored in the original packaging between 20°C and 25°C at 50% relative humidity.

## Recommendations for laminating

Please ensure the print is perfectly dry before laminating. We suggest to let the material dry for at least 48 hours after printing.

## Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.

## Technical Data

<b>Carrier:</b>	embossed polycarbonate, highly stabilized
<b>Thickness:</b>	120 $\mu$ +/- 5 %
<b>Adhesive:</b>	clear solvent acrylic, permanent
<b>Adhesion:</b>	7 N/cm
<b>Liner:</b>	siliconized polyester liner (50 $\mu$ )
<b>Application temperature:</b>	+10 - +40 °C
<b>Temperature durability :</b>	- 40 - +80 °C
<b>Outdoor durability:</b>	<b>3 years</b> (For application as protection film) <b>6 months</b> (For application as floorgraphic film with anti-slippery character)

## Standard Dimensions

1220 mm x 50 m

### KEMICA S.r.l.

Via F.lli Rusjan, 76 - Frazione Rupa  
34070 Savogna d'Isonzo (GO) - ITALIA

Phone: +39 0481 882 501

Fax: +39 0481 882 440

E-Mail: [info@kemicasrl.it](mailto:info@kemicasrl.it)

Internet: [www.kemica.it](http://www.kemica.it)

06/09/2016

The following technical details are issued to the best of our knowledge, however, without any responsibility. Due to the varied and application-related influences the product liability can only be applied to unprocessed material. Therefore, we highly recommend that before every usage a test should be conducted on the original material.