

Product Information

Double-sided tape based on a fleece coated with a solvent-acrylic adhesive with high initial tack.

The adhesive has good ageing, UV and humidity resistance and has high specific adhesion on various materials such as plastic, metal, wood, glass, paper and several foams.

The liner is not sensitive to humidity therefore retroactive creasing is eliminated.

Especially to be emphasised are the following properties:

- Splicing paper for manual or automatic roll change for the manufacturing of corrugated papers.
- Short term temperature resistance up to +200°C and therefore suitable for machinery with longer contact time at the preheating cylinder.
- Mounting of plates, cover-plates, holders and cable trunkings.
- Mounting of polyester, polyether, PVC and polyethylene foams.
- Mounting of displays and promotional articles.
- Suitable for die-cutting.

Technical Data

Carrier:	Fleece	
Adhesive:	Solvent-acrylic	
Liner:	PE-paper, white (120 g/m ²)	
Adhesion [N/cm]:	4,60	+/- 10 %
Thickness [mm]:	0,12	+/- 5 %
Temperature resistance [°C]:	-40 / +120	

Standard Dimensions

1.040 mm x 100 m

1.040 mm x 50 m

Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.