

# POLI-FIX 340

## **Product Information**

Double-sided tape with a carrier material based on a soft PVC-film, coated with an acrylic adhesive with high adhesion.

POLI-FIX 340 offers a high initial tack and excellent resistance against UV, ageing and humidity.

POLI-FIX 340 is universally suitable for long-lasting adhesion to a large variety of materials such as metal, plastic, wood, paper, glass or ceramics.

Especially to be emphasised are the following properties:

- Mounting of plastic profiles in the furniture industry.
- · Mounting of window bars or other decorative parts.
- · Mounting of screens, holders and cable trunkings.
- · Mounting of mirrors in the automotive industry.

### **Technical Data**

Carrier: PVC-film

Adhesive: Acrylic, modified

Liner: Silicone-paper, yellow (95 g/m²)

**Adhesion [N/cm]:** 6,00 +/- 10 %

Thickness [mm]: 0,22 + /-5%

Temperature

resistance [°C]: -40 / +80

#### Standard Dimensions

1.250 mm x 100 m

1.250 mm x 50 m

# Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.

#### POLI-TAPE Klebefolien GmbH

Zeppelinstraße 17

53424 Remagen – GERMANY Phone: +49 (0) 2642 – 9836 0

Fax: +49 (0) 2642 - 9836 37 E-Mail: info@poli-tape.de Internet: www.poli-tape.de 28/07/2011

The following technical details are issued to the best of our knowledge, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material.