

Product Information

Double-sided Polyester adhesive tape coated with an acrylic adhesive of a high tack level.

Beside an excellent ageing, weather and UV-resistance POLI-FIX 343 offers a well specific adhesion for mounting of unpolar plastic such as Polyethylene, Polypropylene and EPDM-rubber.

POLI-FIX 343 is suitable for a long term mounting for a huge variety of materials such as metal, plastics, wood, paper, glass or ceramics, for in- and outdoor use.

Especially to be emphasised are the following properties:

- Mounting of plastic profiles and for furniture.
- Self-adhesive equipment for rubber and EPDM-profiles.
- Mounting screens, holders and cable trunkings.
- Mounting of ABS parts in the automotive industry.

Technical Data

Carrier:	PET-film	
Adhesive:	Acrylic, modified	
Liner:	PP-film, red (80 g/m ²)	
Adhesion [N/cm]:	6,90	+/- 10 %
Thickness [mm]:	0,22	+/- 5 %
Temperature resistance [°C]:	-40 / +120	

Standard Dimensions

1.040 mm x 100 m

1.040 mm x 50 m

Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.