

POLI-FIX 334

Product Information

Double-sided tape with a PET-film as carrier and a liner on both sides.

The permanently elastic acrylic adhesive has an excellent resistance against UV, ageing and humidity.

POLI-FIX 334 offers an excellent tack with a high final adhesion on nearly all type of materials.

Especially to be emphasised are the following properties:

- Mounting of photos, drawings and Ink-Jet prints on plain and flat surfaces.
- Mounting of plates, cover plates, holders and cable trunkings.
- · Mounting of displays and promotional articles.

Technical Data

Carrier: PET-film

Adhesive: Acrylic

Liner: PE-paper, white (120 g/m²)

Adhesion [N/cm]: 2,80 +/- 10%

Thickness [mm]: 0,04 + 1.5 %

Temperature

resistance [°C]: -40 / +120

Standard Dimensions

1.560 mm x 100 m

1.560 mm x 50 m

Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.

POLI-TAPE Klebefolien GmbH

Zeppelinstraße 17

53424 Remagen – GERMANY

Phone: +49 (0) 2642 - 9836 0 Fax: +49 (0) 2642 - 9836 37 E-Mail: info@poli-tape.de Internet: www.poli-tape.de 28/07/2011

The following technical details are issued to the best of our knowledge, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material.