

Product Information

The synthetic rubber has got a high initial tack and offers a high specific adhesion on unpolar plastics.

POLI-FIX 330 guarantees an adhesion on unpolar surfaces such as polyethylene and polypropylene. Due to the adhesive tape is easy to laminate and offers good dimension stability.

Especially to be emphasised are the following properties:

- Mounting of displays, product samples, paper, carton and synthetic materials.

Technical Data

Carrier:	PP-film
Adhesive:	Synthetic rubber
Liner:	Silicone-paper, yellow (95 g/m ²)
Adhesion [N/cm]:	10,00 +/- 10 %
Thickness [mm]:	0,10 +/- 5 %
Temperature resistance [°C]:	-40 / +70

Standard Dimensions

1.500 mm x 100 m

1.500 mm x 50 m

Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.