



## TEC FLOOR 500

### Product Information

Monomeric PVC Film (embossed, white matt, 170  $\mu$ ) with a clear solvent based acrylic adhesive (permanent), laminated on one-sided clay-coated silicone paper liner (135g/m<sup>2</sup>).

Directly printable with solvent, eco-solvent, latex, UV printers; the PVC offers an excellent dimensional stability.

Especially designed for floorgraphic applications with anti-slippery character and scratch resistant surface for mid-term floor decoration and advertising (airports, railway stations, shopping centers).

### Shelf Life

2 years when stored in the original packaging between 20°C and 25°C at 50% relative humidity.

### Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.

### Technical Data

<b>Carrier:</b>	Monomeric white PVC (embossed), highly stabilized, calendered
<b>Thickness:</b>	170 $\mu$ +/- 5%
<b>Adhesive:</b>	clear solvent acrylic, permanent
<b>Adhesion:</b>	7 N/cm
<b>Liner:</b>	one-sided clay-coated silicone paper (135 g/m <sup>2</sup> )
<b>Application temperature:</b>	+10 - +40 °C
<b>Temperature durability :</b>	- 40 - +80 °C
<b>Outdoor durability:</b>	<b>6 months</b> (For application as floorgraphicfilm with anti-slippery character)

### Standard Dimensions

1370 mm x 50 m  
1550 mm x 50 m

#### KEMICA S.r.l.

Via F.lli Rusjan, 76 - Frazione Rupa  
34070 Savogna d'Isonzo (GO) - ITALIA

Phone: +39 0481 882 501  
Fax: +39 0481 882 440

E-Mail: [info@kemicasrl.it](mailto:info@kemicasrl.it)  
Internet: [www.kemica.it](http://www.kemica.it)

23/15/2019

The following technical details are issued to the best of our knowledge, however, without any responsibility. Due to the varied and application-related influences the product liability can only be applied to unprocessed material. Therefore, we highly recommend that before every usage a test should be conducted on the original material.