



## TEC ROLL 3150 T/HT

### Product Information

Transparent Polyethylene film for the application of self adhesive lettering and logos. The tape is suitable for all types of vinyl.

Especially to be emphasised are the following properties:

- The plasticiser resistant adhesive guarantees a strong initial tack to all types of vinyl films. The Application Tape is easily removed without leaving any residue, even after being left for a period of time.
- The transparent film conforms well to irregular surfaces and provides a high stretching strength to enable accurate positioning of the work.
- The adhesive is coated in a special way which ensures that the tape is easily unrolled thereby eliminating static problems in handling.

### Technical Data

Carrier:	Polyethylene film
Adhesive:	Acrylic, modified
Adhesion [N/cm]:	1,00 +/- 10 %
Thickness [mm]:	0,16 +/- 5 %

### Standard Dimensions

1.220 mm x 100 m  
1.000 mm x 100 m

### Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.

#### KEMICA S.r.l.

Via F.lli Rusjan, 76 - Frazione Rupa  
34070 Savogna d'Isonzo (GO) - ITALIA

Phone: +39 0481 882 501  
Fax: +39 0481 882 440

E-Mail: [info@kemicasrl.it](mailto:info@kemicasrl.it)  
Internet: [www.kemica.it](http://www.kemica.it)

20/01/2017

The following technical details are issued to the best of our knowledge, however, without any responsibility. Due to the varied and application-related influences the product liability can only be applied to unprocessed material. Therefore, we highly recommend that before every usage a test should be conducted on the original material.