

Product Information

Double-sided tape based on a fleece coated with a solvent-acrylic adhesive.

The adhesive has good ageing, UV and humidity resistance and is suitable for mounting of polar and unpolar materials such as plastic, metal, wood, glass, paper and ceramic.

The liner can be removed easily and without tearing. It is not sensitive to humidity therefore retroactive creasing is eliminated.

Especially to be emphasised are the following properties:

- Splicing of paper, cardboard and films.
- Laminating of roll material such as felt, film, tissue, paper and cardboard.
- Mounting of displays and promotional articles.
- Self-sealing finish of polyester, polyether, PVC and polyethylene foams.
- Mounting of PVC skirting boards or base boards.

Technical Data

Carrier:	Fleece
Adhesive:	Solvent-acrylic
Liner:	PE-paper, white (120 g/m ²)
Adhesion [N/cm]:	4,20 +/- 10 %
Thickness [mm]:	0,10 +/- 5 %
Temperature resistance [°C]:	-40 / +120

Standard Dimensions

1.040 mm x 100 m

1.040 mm x 50 m

Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.