

POLI-TRANS® 315 INKJET PREMIUM DARK A4 316 INKJET PREMIUM DARK A3

GENERAL USE

INKJET PREMIUM DARK is recommended to be used with inkjet printers using pigment inks. Produce high resolution transfers for application to dark coloured textiles. Transfers can be applied to cotton, polyester and poly/cotton textiles. **INKJET PREMIUM DARK** can also be contour cut using a vinyl cutter.

Always single sheet feed transfer papers. Allow the ink to dry and do not apply until 10 minutes after printing.

PRINTER SETTINGS

In general we suggest the printer settings are set to plain paper and fine or photo quality. Settings on printers vary, therefore produce a test print to determine the best settings.

APPLICATION

Print selected image on the white side of the transfer film, do not mirror image. To avoid showing white areas when applied to the T-shirt, trim around the design. Use a vinly cutter, with low force, to cut around complex shapes. Remove backing film and position design on T-shirt. Always cover the transfer with silicone paper during heat press application.

- Press at 160 °C (320 Fahrenheit)
- Time 10 sec.
- Medium pressure
- Remove silicone paper cold
- Not suitable for textiles dyed with sublimation inks

WASHING

- Using pigment inks Textiles can be washed up to 60 degrees, inside out
- Using waterbased inks Textiles should be machine washed inside out in a cool wash only

All information given is for guidance purposes only. Many different factors are involved in producing transfers, therefore we recommend customers to perform their own tests. These instructions are not legally binding. Information given is subject to change without notice.