



THERMO-TAPE

Product Information

Flexible PET-film with a high tack Silicon adhesive. The adhesive has an excellent resistance to chemicals, ageing, humidity and high temperature.

Suitable for positioning of Flock- and Flex-products before and during thermal transfer.

Technical Data

Carrier:	PET-film, green	
Adhesive:	Silicon-Rubber	
Adhesion [N/cm]:	3,60	+/- 10 %
Thickness [mm]:	0,06	+/- 5 %
Temperature-resistance [°C]:	max. 200	

Standard Dimensions

- 9 mm x 66 m
- 12 mm x 66 m
- 19 mm x 66 m
- 25 mm x 66 m

Safety Data Sheet

When used under normal conditions, this product does not generate or release any dangerous substances or hazardous chemicals. This is a non-hazardous product in accordance with the current GefStoffV and EU criteria. Therefore it is not necessary to prepare a Material Safety Data Sheet for this product. The Safety Data Sheet serves only to comply with the regulation to supply information in accordance with REACH Regulation (EC) No. 1907/2006 and is available on request. This product is not a hazardous product with regards to transportation legislation; neither does it contain substances that are hazardous to water within the meaning of the federal water act. After use, dispose of the waste product in accordance with the local / national authorities.

POLI-TAPE Klebefolien GmbH
Zeppelinstraße 17
53424 Remagen – GERMANY

Phone: +49 (0) 2642 – 9836 0
Fax: +49 (0) 2642 – 9836 37

E-Mail: info@poli-tape.de
Internet: www.poli-tape.de

28/07/2011

The following technical details are issued to the best of our knowledge, however, without any responsibility for results due to several different kinds of material and application processes. Therefore, we highly recommend that before every usage a test should be conducted on the original material.